

24 VDC Power Supply

FEATURES

- DIN Rail “Snap Track” mounting
- Power supply – 24 VDC, 15 W
- Power consumption – 10 VA maximum

APPLICATIONS

Power supply for BLH Nobel weigh system instruments

- PS-1020
- PS-1045
- PS-1050

DESCRIPTION


PS-121 Modules supply 24 VDC power for the BLH Nobel PS transmitter family: PS-1020, PS-1045, and PS-1050. Each module is capable of powering a single PS Transmitter with six transducers or two PS Transmitters with four transducers.

Units are factory configured for either 115 or 220 VAC operation. A spare fuse is included.



“Snap on” DIN Rail mounting significantly reduces system installation and start-up time. Close mounting proximity to PS Transmitters is recommended to reduce excessive wiring and reject electronic noise interference.


CONFIGURATION



24 VDC Power Supply

SPECIFICATIONS		PARAMETER	VALUE
ELECTRICAL		PARAMETER	VALUE
Input Voltage*	115 or 220 VAC – 50/60 Hz	ENVIRONMENTAL	
Output Voltage	24 VDC unregulated	Operating Temperature	-10 to +40°C (+14 to +104°F)
Power Consumption	10 VA max.	Storage Temperature	-20 to +50°C (-4 to +122°F)
Maximum Power	15 W	Humidity	85% RH, non-condensing
Isolation	Class II	APPROVALS	
Category	Category II	CE	EN 50081-1, 50082-2, 61010-1
Fuse	T200 mA (115 VAC) or T110 mA (220 VAC) Size 5×20 mm	BLH Nobel is continually seeking to improve product quality and performance. Specifications may change without notice.	

* Input voltage is factory configured



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.