

Load Cells for Offshore Applications

Product Overview



SMART SOLUTIONS FOR
DEMANDING INDUSTRIES

BLH NOBEL
A VPG Brand

Load Cells for Offshore Applications

At BLH Nobel,

we have been supplying load cells to the offshore industry for more than 40 years. Today we are a leading global supplier of high quality customized products.

Our solutions are often found in winches and mooring applications as well as cranes.

Solutions tailored to your application:

- Extensive application knowledge
- Tailor-made load cells
- Field replaceable amplifiers
- High ingress protection

Applications

- Cranes
- Winches
- Mooring
- Cable laying
- ... more



WE BELIEVE IN **RELIABILITY.**

That's why our products are designed to withstand the toughest and roughest conditions such as vibration, overload and humidity.



WE BELIEVE IN **CONTROL.**

That's why our load cells provide high accuracy, repeatability and correct measurements for weight and force.



WE BELIEVE IN **QUALITY.**

That's why we design, build, and deliver a custom made solution with very competitive lead times. Our strength is our engineering expertise, our flexible and agile organization, tailoring the solution to your specific need.

Our load cell engineers design products that offer the best combinations of robustness, reliability, and accuracy to fit specific requirements of forces or weights, space, accuracy, and environmental conditions. Whether your requirements involve a crane application or a subsea application, we have the expertise












needed to provide a solution. We offer customers the benefits of our experience in solving complicated application problems (as well as standard ones) using the principles of KOSD, KIMD, KISD, KEND, and many other types of load cells.

All our load cells can be delivered with embedded amplifiers with an

output signal of 4-20 mA; either fixed or field replaceable (plug n' play) version.

All load cells are available with both ATEX and IECEx.

Ingress protection IP67 is standard, IP68 is available. All load cells are delivered with 3.1 material certificates, 3.2 are optional.

| Load Cell Type | Description | Operation Principle |
|--|--|--|
| <p>KOSD</p>  | <p>Double-ended shear beam with circular cross section</p> <p>Robust construction with high ingress protection for force measurement, e.g., mooring, winches, cranes, etc.</p> <ul style="list-style-type: none"> • Capacity: 0.5 kN to 20 MN • Combined error: 0.5% to 2.0% of R.O. • Cable or connector • ATEX and IECEx approved • IP67 or IP68 |  |
| <p>KIMD</p>  | <p>Double-ended shear beam with I-beam cross section</p> <p>High-accuracy load cell for weighing and force measurement, e.g., cranes</p> <ul style="list-style-type: none"> • Capacity: 0.5 kN to 20 MN • Combined error: 0.2% to 0.5% of R.O. • Cable or connector • ATEX and IECEx approved • IP67 |  |
| <p>KISD</p>  | <p>Double-ended, double-cantilever shear beam with I-beam cross section</p> <p>High accuracy load cell for weighing and force measurement, e.g. cranes, cable laying, etc.</p> <ul style="list-style-type: none"> • Capacity: 0.5 kN to 1 MN • Combined error: 0.1% to 0.3% of R.O. • Cable or connector • ATEX and IECEx approved • IP67 |  |
| <p>KEND</p>  | <p>Tension Link</p> <p>High accuracy load cell for tension force applications</p> <ul style="list-style-type: none"> • Capacity 10 kN to 2 MN • Combined error 0.1% • Cable or connector • ATEX and IECEx approved • IP67 or IP68 |  |
| Amplifier Type | | Description |
| <p>LCAMP100</p>  | | <p>Outputs: All load cells are optional one or two (redundant) bridge outputs. Standards are mV/V, analog 4–20 mA are optional.</p> |
| <p>LCAMP100</p>  | <p>Field replaceable embedded digital analog amplifier. Single or redundant applications.</p> <ul style="list-style-type: none"> • 2 wire 4–20 mA output • 10 point linearization • HART communication • 5 ms response time • ATEX and IECEx approved [KXXD-RA(D)] | |
| <p>LCAMP300</p>  | <p>Fixed embedded digital analog amplifier. Single or redundant applications.</p> <ul style="list-style-type: none"> • 2 wire 4–20 mA output • 3 point linearization • 5 ms response time • ATEX and IECEx approved [KXXD-FA(D)] | |

SMART SOLUTIONS FOR
DEMANDING INDUSTRIES

BLH NOBEL
A VPG Brand



Contact

Americas: blhnobel.usa@vpgsensors.com

Europe: blhnobel.eur@vpgsensors.com

Asia: blhnobel.asia@vpgsensors.com

blhnobel.com

DISCLAIMER: ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE. Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein. VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.** Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com. No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG. The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.

VPW-PL0454-1411