BLH NOBEL
A VPG Brand

G6-PM

ADVANCED PROCESS CONTROL INSTRUMENTS FAMILY

FEATURES

- Modular system with flexible configuration
- Up to 8 weighing/force measurement channels per unit
- Synchronized sampling
- Fast update rate – up to 800 updates per second
- Graphical User Interface – color LCD display with backlight
- Data entry through touch screen and/or functional Keypad
- Integrated flexible digital I/O
- Communication: Ethernet, Profibus, PROFINET DeviceNet, Modbus, USB, RS485, Modbus/TCP, EtherNet/IP
- Easy parameter backup and restoration via USB port or internal memory



Panel Mount (PM)

CE

APPLICATIONS

- Process weighing and control
- Force measurement
- Web tension measurement and control
- Automation
- Force vector calculations
- High dynamic force measurement
- High speed batching / blending systems

DESCRIPTION

The BLH Nobel G6 family of process control instruments offers high speed, high performance control for industrial weighing/force measurement applications plant wide. G6 units set new standards geared for today's application demands and tomorrow's expanding requirements.

A large (5.7 in) color touch screen facilitates quick, easy operation and simplifies parameter changes. The screen displays up to 4 weighing/force channels simultaneously, allowing the user full control of multiple process vessels. The large touch screen provides good visibility of the process and easy navigation through parameter menus and settings.

G6 instruments accommodate up to six different, easily installed, modules for advanced performance, more functional channels, custom applications, or repair. This provides customers with a highly flexible, upgradeable, single instrument system capable of weighing up to eight independent vessels or scales. Inputs and outputs can be configured according to customer requirements.


A wide variety of industrial communication interfaces (Ethernet, RS485), Protocols (Modbus RTU, Modbus TCP, EtherNet/IP) and Fieldbuses (Profibus, PROFINET or DeviceNet) are available.

Software upgrades can be downloaded to the instrument from our website, or be transferred to the G6 unit via a standard USB port connection.

Custom software designed to customer requirements for special applications is available upon request.

G6 instruments have two base mounting options: DIN Rail and Panel Mount. The panel mount is IP65 rated, while the DIN rail-mount is IP20 rated. Units can be configured for either 24 VDC or 115/230 VAC operation.

CONFIGURATION



Technical contact: blhnobel.usa@vpgsensors.com,
Europe: blhnobel.eur@vpgsensors.com, Asia: blhnobel.asia@vpgsensors.com

G6-PM

SPECIFICATIONS

PARAMETER	VALUE
Enclosure types	PM Panel mount
Dimensions W × H × D	294 × 227 × 152 mm
Enclosure design	Aluminum housing, plastic panel
ENVIRONMENTAL	
Temperature range – Rated performance	–10 to +50°C
Temperature range – Storage	–25 to +85°C
Protection	IP65 (panel)
EMC	Class A group 1 equipment, industrial electromagnetic environment (acc. to EN 61326-1:2013)
Markings	CE
Display	Color TFT LCD screen with back-lighting, 5.7 in 320 × 240 pixels
Keyboard	Touch screen and 34 membrane keys
POWER	
DC SUPPLY module	24VDC ±15%, 40 W
AC SUPPLY module	115/230 VAC 50/60 Hz, 40 W
CPU MODULE	
Interfaces	Isolated
RS485 port	For process data and control
Protocol	Modbus RTU
Baud rate	Up to 115 kbaud
USB, supported units	Version 2.0
Keyboard	USB keyboard for PC
Memory stick	USB type for PC For backup and restore of set-up parameters. For change to a new program version
Ethernet	For process data and control
Protocol	Modbus TCP and EtherNet/IP
Field bus options	For process data and control
Available field busses	Profibus, PROFINET or DeviceNet

PARAMETER	VALUE
WFIN1 (1 INPUT) AND WFIN2 (2 INPUTS) WEIGHT/FORCE INPUT MODULES	
Max. no. of load cells	8 per channel
Excitation voltage	5 VDC
A/D conversion	3.9 kHz, 16,000,000 units (24 bits)
Input range	±7 mV/V
Update rate	2.3 to 300 readings per second
No. of weight channels	up to 8 channels
Sensitivity	0.1 µV
Zero drift	<10 nV/V/K
Span drift	<2 ppm/K
Digital I/O	4 inputs, 24 V, isolated with common return 2 outputs, 24 V, max. 100 mA, isolated with common return
HSWF2 HIGH SPEED WEIGHT/FORCE INPUT MODULE	
Max. no. of load cells	4 per channel
Excitation voltage	10 VDC
A/D conversion	20 kHz, 16,000,000 units (24 bits)
Input range	±4.5 mV/V
Update rate	12.5 - 800 readings per second
No. of weight channels	Up to 8 channels
Sensitivity	0.1 µV
Zero drift	<10 nV/V/K
Span drift	<2 ppm/K
Type	4 inputs, 24 V, isolated with common return 2 outputs, 24 V, max. 100 mA, isolated with common return
DIO8 MODULE, DIGITAL INPUT AND OUTPUT MODULE	
Separate I/O module	2 units can be used
Digital I/O	8 inputs, 24 V, isolated with common return 8 outputs, 24 V, max. 100 mA, isolated with common return
AOUT1 / AOUT4 ANALOG OUTPUT MODULES	
Number of channels	1 or 4, separately isolated channels
Resolution	65,000 units, 16 bits
Voltage output	0 to 10 V, –10 to 10 V, >1 kΩ load
Current output	4 to 20 mA, 0 to 20 mA, –12 to 20 mA or –20 to 20 mA <500 Ω load
Update rate	Analog input update rate, adjustable smoothing filter

ORDERING INFORMATION

Part Number Nomenclature: G6-PM-FB-S1-S2-S3-S4-S5-S6-P-SW

Code	Type	Part Number Reference	Description
G6	Instrument type	G6	—
PM	Enclosure type	PM	Panel mount
FB	Fieldbus interface	0 P N D	None Profibus PROFINET DeviceNet
Si	Slot 1 to 6 type	0 2 3 4 6 7 8	Blank HSWF2—High speed weight/force, dual input module WFIN1—Weight/force, single input module WFIN2—Weight / force, dual input module AOUT1—Analog output, single channel AOUT4—Analog output, 4 channels DIO8—Digital input and output module
P	Power supply	D A	DC power supply AC power supply
SW	Software version	W F S	Weighing Force Special version (contact factory for option code)

Example of actual part number: G6-PM-0-4-8-0-0-0-0-D-F

Where:

G6 instrument (G6)

Panel mount (PM)

No field bus (0)

Slot 1 = WFIN1 (4)

Slot 2 = DIO8 (8)

Slot 3 = Blank (0)

Slot 4 = Blank (0)

Slot 5 = Blank (0)

Slot 6 = Blank (0)

Power = DC supply (D)

Software = Force

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “VPG”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG’s terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG’s knowledge of typical requirements that are often placed on VPG products. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.