

## Gate-Weigh® LAN Controller

### FEATURES

- Single port communication interface for multiple transmitters/indicators
- Constant update and storage of node data eliminates polling/response delay time
- Modbus Plus or RTU protocol and Allen-Bradley Remote I/O
- Self-configuring BLH Nobel Digi-System Plus Network

### APPLICATIONS

- Plant-wide weigh system LAN
- Controller
- 16 system interface with PLC or DCS systems

### DESCRIPTION


The LCp-400 Gate-Weigh is a multi-scale local area network controller and communication gateway. This network bridge device uses BLH Nobel Digi-System Plus network communication technology to continuously scan up to 16 weigh system nodes and is equipped with an Allen-Bradley Remote I/O or Modbus Plus network port output. The LCp-400 is also available with a conventional MODBUS RTU serial output.

Digi-System Plus network is a self configuring, enhanced RS-485 based communication link that operates at a rate of 57.6 Kbps over distances of up to 4000 ft. Operationally, the LCp-400 scans each node on the network continuously and updates internal register locations with current weigh, diagnostics and status data. Through the gateway port, a host PLC, PC or DCS can perform read/write commands to retrieve data without polling and response delays typical in other multi-drop network arrangements.




In addition to the network communication and gateway functions, the LCp-400 is also a centralized scanning terminal that displays weight & status information from any node on the network. Currently, the LCp-400 Digi-System Plus network is compatible with the LCp-100 Indicator/Transmitter, LCp-200 Indicator Controller, DXp-40 Transmitter, and PS-2010 Controllers.

### CONFIGURATION



## Gate-Weigh® LAN Controller

SPECIFICATIONS		PARAMETER	VALUE
<b>DISPLAY</b>		<b>PARAMETER</b>	<b>VALUE</b>
Type	high intensity amber LED display	<b>BLH DIGI-SYSTEM PLUS NETWORK</b>	
Active Digits	7 digit alpha numeric 0.59 in high for weight: 8 digit alpha numeric 0.39 in high for status	Serial RS-485	two wire
<b>ENVIRONMENT</b>		Baud Rates	9600, 28800, or 57600
Operating Temperature	-10 to 55°C (15 to 131°F)	Protocol	proprietary
Storage Temperature	-20 to 85°C (-5 to 185°F)	Addressing	up to 16 nodes
Humidity	5 to 90% RH non-condensing	<b>GATEWAY INTERFACES</b>	
Voltage	117/230 VAC ±15% @ 50/60 Hz	Allen-Bradley	remote I/O – ¼ logical rack
Power	15 W max.	Modbus RTU	slave
<b>ENCLOSURE</b>		Modbus Plus	peer-to-peer
Dimensions (std.)	4.63×8.40×6.5 in H×W×D	<b>APPROVALS/CERTIFICATIONS</b>	
NEMA 4/4X, 12 (opt)	8.5×13.5×10.45 in H×W×D	FM (Factory Mutual)	3611 (Class I, II, III; Div.1,2; Groups A-G)
<b>MATERIALS</b>		CSA	C22.2 (Class I, II, III; Div.1,2; Groups A-G)
Aluminum case and bezel overlay meets 94 V-0 rating			



## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com).

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.